


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B41J 2/21	A1	(11) International Publication Number: WO 00/30856 (43) International Publication Date: 2 June 2000 (02.06.00)
(21) International Application Number: PCT/GB99/03883 (22) International Filing Date: 22 November 1999 (22.11.99) (30) Priority Data: 9825359.4 20 November 1998 (20.11.98) GB (71) Applicant (for all designated States except US): XAAR TECHNOLOGY LIMITED [GB/GB]; Science Park, Cambridge CB4 0XR (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): TEMPLE, Stephen [GB/GB]; The Windmill, Impington, Cambridge CB4 9NU (GB). (74) Agents: GARRATT, Peter, Douglas et al.; Mathys & Squire, 100 Gray's Inn Road, London WC1X 8AL (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: METHODS OF INKJET PRINTING



(57) Abstract

In ink jet printing, a UV curable undercoat is first deposited on a substrate. The ink and undercoat are cured together. The thickness of the undercoat varies inversely with the thickness of the ink, so that a flat print surface is achieved. Application of an undercoat may be disabled on text material, to preserve edge definition.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

- 1 -

METHODS OF INKJET PRINTING

The present invention relates to methods of inkjet printing.

There are a number of well-known inkjet printing techniques in which the number of ink droplets deposited per unit area is controlled to vary the optical density of printing. With multiple printheads, print colour can similarly be controlled.

5 A problem that is frequently encountered is that the final print quality is heavily dependent on whether and to what extent individual ink droplets spread on the substrate and coalesce with their neighbours. The behaviour of any one ink droplet in this respect is dependent to a considerable extent upon the number of other ink droplets being deposited in the same vicinity. Moreover, this behaviour is also influenced by
10 microscopic variations in the mechanical and chemical properties of the substrate (especially the roughness of the substrate surface and the surface tension), so that the degree of spread and coalescing of droplets is not constant or reproducible, even where the pattern of neighbouring droplets is unchanging.

To provide a degree of control over the behaviour of ink droplets on the
15 substrate, and indeed during the droplet deposition process, it is common to use inks that have a defined curing, fixing or hardening phase, such as ultra-violet curable ink. Whilst remaining within the inkjet printhead, during flight and for an initial interval upon the substrate, this liquid UV curable ink remains in what might be termed a "wet phase". At the appropriate time, the printed droplets are exposed to UV radiation, effecting
20 through UV curing a transformation from the "wet phase" to a "dry phase". A similar effect can be achieved with hot melt inks where the transformation from "wet phase" to "dry phase" is controlled by temperature, or with dual-component inks where exposure to a hardening or fixing component effects the transformation. In this specification, the
25 terms "wet" and "dry" will be employed to denote the respectively less and more viscous states of an ink or other printing material which has a defined curing, fixing or hardening phase.

It is an object of one aspect of the present invention to provide an improved method of inkjet printing in which the variability of droplet behaviour on the substrate is

- 2 -

significantly reduced.

Accordingly, the present invention consists, in one aspect, in a method of ink jet printing on a substrate, comprising the steps of forming a wet undercoat layer on the substrate; depositing onto the undercoat layer, whilst the undercoat layer remains wet, a pattern of wet ink droplets and subsequently transforming the undercoat layer and deposited ink droplets to a dry state.

The undercoat layer may be formed using a variety of well known techniques, such as offset or bar coating, although it is preferably formed, wholly or in part, through ink jet printing.

The undercoat will typically be colourless, although this is not essential. A white undercoat may, for example, be useful in concealing colour variations over the substrate. If the undercoat is a different colour than the intended print substrate, there may be a requirement for further image processing of the print data prior to printing.

It is found that the spreading and coalescing of wet ink droplets on a wet undercoat is considerable more uniform and reproducible than on a bare substrate.

In many applications, the described problem of variable behaviour of deposited ink droplets is noticeable at certain densities of printing but not at others. It may be, for example that at low densities, the deposited ink droplets are sufficiently spaced that they never coalesce. At high densities, the ink droplets overlap sufficiently for them always to coalesce. It is over an intermediate range of densities that the problem of variable droplet behaviour produces noticeable artefacts.

Accordingly, in a preferred form of the invention, the step of forming a wet undercoat layer comprises the formation of a layer that varies spatially with the pattern of ink droplets to be deposited.

Suitably, the undercoat layer is formed on selected regions of the substrate but not on other regions, the selection of regions to receive an undercoat being dependent upon the pattern of ink droplets.

Advantageously, the thickness of the undercoat layer varies spatially with the pattern of ink droplets to be deposited.

When - for example - UV printing with 100% reactive inks, a glossy finish is

- 3 -

usually produced. Reflected light from the surface reveals variations in thickness across the image.

It is observed that in such and certain other applications, the print quality can be further improved if the thickness of the undercoat layer varies generally inversely with the number of ink droplets to be deposited in a local region. In this way, it can be arranged that the total thickness of undercoat plus ink, remains sensibly constant over the substrate. This step is particularly beneficial where variations of print density are relatively gradual, such as in the printing of photographs or other images. Where there are high spatial frequencies in the print content – such as with text – and the desired changes in print density are abrupt rather than gradual, the step may be less beneficial or - indeed - harmful.

Thus, in a further form of the invention, the variation in the thickness of the undercoat layer with the pattern of deposited ink droplets, is disabled in regions where the print content to be represented by the pattern of ink is determined to comprise text or other high spatial frequency matter.

The invention will now be described by way of example with reference to the accompanying drawings, in which:

Figure 1 is a diagram illustrating a method of ink jet printing in accordance with one aspect of the invention;

Figure 2 is a schematic cross section through a substrate printed in accordance with one aspect of the invention; and

Figure 3 is a cross section similar to Figure 2, illustrating a modification.

Figure 1 is a diagram illustrating a method of ink jet printing in accordance with one aspect of the invention. In this example, the substrate is a plastic card shown at 100 and formed of PVC or ABS.

- 4 -

Firstly, an undercoat in the form of a thin layer of a UV curable carrier is applied to the substrate at undercoating station 102, in advance of ink jet printing.

Two ink jet printheads 104, 106 are angled to the substrate travel direction 108 to give 360dpi resolution. The printheads are monochrome and print dark and light inks of a single colour respectively. The inks may for example have the same constituents but different proportions of pigment. The printheads may for example take any of the forms disclosed in EP-A-0 277 703 or EP-A-0 278 590 and are preferably arranged for multi tone printing as shown in EP-A-0 422 870, which specifications are all hereby incorporated by reference. The two print heads print wet-on-wet, and, after a delay determined by the distance to the UV lamp 108 and the print speed, the combined layer is cured. The delay before curing is typically less than one second. A typical cure energy is 1.25 J/cm^2 with a cure time of less than one second.

With this arrangement, it has been found possible to print a wedge of a single colour on a plastic card. By "wedge" is meant a solid block with the print colour varying continuously in the direction of printing. This is an exacting test of the ability of a printer to resolve small differences in colour or luminance without print artefacts. Using a method according to this invention, the printed wedge is found to be smooth having no visible dot structure and being closely linear. The results are subjectively of comparable quality to that obtained with offset lithography.

A key feature necessary to achieve this result is the wet undercoat layer. This allows drops to spread uniformly without regard to their neighbours. When printing on a dry substrate, spreading and merging of drops depends greatly on the amount of ink in neighbouring pixels. Use of a wet undercoat homogenises the behaviour.

A number of droplets from one or both printheads firing light and dark inks respectively are used to form a printed dot on the substrate. If each printhead is capable of firing n levels (that is to say $n - 1$ drops per dot), there are a theoretical n^2 levels of tone. For example, for $n = 4$, we have:-

- 5 -

Drops of Ink.1	0	1	2	3	0	1	2	3	0	1	2	3	0	1	2	3
Drops of Ink.2	0	0	0	0	1	1	1	1	2	2	2	2	3	3	3	3
Resulting Tone:	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15

This number of levels can only be made available practically, if the behaviour on the substrate of the droplets from each printhead is carefully controlled. This is achieved by the use of a wet undercoat. Without such control, it has proved possible to use only some of the available levels.

Printing with all of these levels gives surprising results; as has been noted, print quality comparable with offset lithography is achievable. It will be recognised that the number of levels required to produce a desired print quality will vary according to the application.

In some cases, the counter-intuitive effect is observed of the darkness of the wedge reducing for increasing amounts of ink. This is a result of complex interactions between the droplets of the two inks, which remain even within the controlled substrate environment provided by the wet undercoat. Any such anomalous behaviour can be corrected according to a further aspect of the invention by measuring the density of the output tone for each of the used levels (as shown above) and applying these values as an inverse relationship to the picture values.

A combination of the features mentioned above has resulted in successful printing with twelve levels of two inks. However, there are further aspects of the invention which produce further improvement or simpler printing.

The use of light and dark inks of the same colour is not an essential feature of the invention; the use of a wet undercoat provides an advantage with a single printheads or with multiple printheads corresponding respectively with three, four, six or other known colour component schemes.

It is also possible to use a printhead of the kind disclosed in WO 95/25011 (which specification is hereby incorporated by reference) with firing pulses having a duration of less than L/c to produce "fractional" drops. This can be used (a) to reduce

- 6 -

the size of the smallest dot (instead of using light ink), or (b) to linearise the tone curve as described above but by altering the waveform rather than the picture. This method has the further merit that it reduces the total ink put down and would therefore increase the total number of levels available from a given head arrangement. Suppose that it takes 7 droplets per dot to print full density using actuating waveforms of equal duration: if the duration of the actuating waveform used to eject the first droplet is halved, and others reduced between 0.5 and 1, then the total ink volume deposited by 7 droplets is now less and, instead, 10 or 12 dpd (droplets per print dot) might be required to reach full black. The performance of this simple head is comparable with a two-tone ink approach.

The undercoat can be applied by a roller or wiper or by a wide variety of other known techniques. In one form of this invention, however, a clear undercoat layer is deposited using a further ink jet printhead. The "tone" of this layer would be such as to "top up" the ink film where little is to be printed. For example, suppose the total ink allowed for all colours is 300%, then the undercoat printhead would print (300 -C-M-Y- K- c - m -y - k), where C= dark cyan, c = light cyan etc.

A simple way of achieving a top up undercoat is to create a "luminosity" version of a picture (for example by converting a colour picture to grey using well known image processing software). This may be regarded as a map showing the amount of ink to be deposited at each point in the image. If this map is inverted (by subtraction from an appropriate fixed value), a desired depth map is then provided for the undercoat.

If the example is taken of monochrome printing (or a single component of a multi-component colour scheme), it is useful to control the number of ink dpd and undercoat dpd such that the aggregate number of dpd remains constant.

Referring to Figure 2, an arrangement is shown in which the thickness of the receiver undercoat 200 deposited onto the substrate 202 is varied with the thickness of ink 204 such that a constant overall thickness is achieved and, thereby, a flat top surface. In many applications, especially with plastic substrates, this is found to produce excellent print quality.

The controlled use of a binary ink system (ink + clear or white undercoat), such

- 7 -

that the aggregate number of droplets per print dot is maintained sensibly constant, is felt to have important advantages. It will be recognised that the same technique can be applied to other binary systems in which the two components have different optical density, as well as to more complex systems having more than two components. The order in which the different components are deposited on the substrate may sometimes be varied. Thus a flat top surface could be achieved by the use of a clear top coat. It will be understood however that such an arrangement will not provide the advantages mentioned previously of a wet undercoat.

Whilst, the use of a wet undercoat (or a co-deposited clear component) offers important advantages, benefit can be achieved by the application of an undercoat which varies in thickness to accommodate the local ink thickness, even if that undercoat is not wet as the ink is deposited. As seen in Figure 4, an undercoat layer can be applied to a substrate to provide "pits" to receive the necessary numbers of droplets from a downstream ink jet printhead.

It has been discovered many of the above-described techniques work differently with different types of print material. It is found for example that whilst the use of an undercoat is particularly effective in printing photographs or similar images, it is less effective (and indeed sometimes unhelpful) in text printing. In one embodiment of the invention, therefore, the nature of the print content is determined and the application of an undercoat is disabled in areas of text. This preserves edge definition. It has been found advantageous not print to undercoat wherever there is high frequency detail (whether arising from text or more generally), possibly extending this to a "halo" of dry base around the text or other region of high frequency detail. The print content may be analysed for this purpose using a spatial filtering technique to determine a map of regions where the use of an undercoat is to be disabled. That map can be spatially filtered to "spread" the uncoated area, for example by means of a simple FIR (Fixed Impulse Response) filter.

The undercoat used in the various examples described above may, if clear, take the form essentially of the diluent used in the corresponding ink.

- 8 -

An example is given in Table 1 below of a four colour ink scheme, with a white undercoat for use in accordance with the invention.

TABLE 1 (proportions by wt%)

MATERIAL	BLACK	CYAN	MAGENTA	YELLOW	UNDERCOAT
ACTILANE 422	-	-	-	-	18.55%
ACTILANE 430	12.50%	12.50%	12.50%	12.50%	-
ACTILANE 251	12.50%	12.50%	12.50%	12.50%	15.00%
TEGORAD 2200	0.40%	0.40%	0.40%	0.40%	0.40%
SARTOMER 506*	39.70%	40.00%	38.35%	41.48%	-
SARTOMER 306	23.00%	22.90%	23.00%	22.0%	-
SPEEDCURE ITX	2.00%	-	-	-	-
QUANTACURE EHA	3.00%	-	-	-	-
IRGACURE 907	5.00%	-	-	-	10%
REGAL 250R	1.50%	-	-	-	-
SOLSPERSE 24000	0.38%	0.60%	0.75%	0.30%	1.05%
SOLSPERSE 5000	0.03%	0.11%	-	-	-
IRGALITE BLUE GLVO	-	1.00%	-	-	-
HOSTAPERM RED E5B 02	-	-	2.50%	-	-
PALITOL YELLOW D1155	-	-	-	0.75%	-
SOLSPERSE 22000	-	-	-	0.07%	-
LUCERIN TPO	-	5.00%	5.00%	5.00%	-
DAROCURE 1173	-	5.00%	5.00%	5.00%	-
N-VINYL PYRROLIDONE	-	-	-	-	20%
WHITE PIGMENT	-	-	-	-	35%

A further example is given in Table 2, below, of a monochrome, light and dark ink scheme with a clear undercoat.

TABLE 2 (proportions by wt%)

MATERIAL	BLACK 1	BLACK 2	UNDERCOAT
SOLSPERSE 2400	0.38%	0.76%	-
SOLSPERSE 5000	0.03%	0.06%	-
ACTILANE 430	12.5%	12.5%	10.2%
ACTILANE 251	12.5%	12.5%	15.3%
SARTOMER 306	23%	22.3%	23.4%
SARTOMER 506	39.7%	38.5%	40.9%
TEGORAD 2200	0.4%	0.4%	-
LUCERIN TPO	-	0%	5.1%
DAROCURE 1173	-	0%	5.1%
IRGACURE 907	5%	5%	-
SPEEDCURE ITX	2%	2%	-
QUANTACURE EH	3%	3%	-

- 9 -

It should be understood that this invention has been described by way of examples only and that a wide variety of modifications are possible without departing from the scope of the invention. Thus, whilst the invention has been particularly described with reference to UV curable inks and undercoats, the invention is applicable to hot melt inks, and other inks having defined wet and dry phases. A suitable undercoat will typically take the same form as the ink, with the pigment or other colourant removed or replaced by white pigment or other colourant.

CLAIMS

1. A method of ink jet printing on a substrate, comprising the steps of forming a wet undercoat layer on the substrate; depositing onto the undercoat layer, whilst the undercoat layer remains wet, a pattern of wet ink droplets and subsequently transforming the undercoat layer and deposited ink droplets to a dry state.
2. A method according to Claim 1, wherein the undercoat layer is formed at least in part, through ink jet printing.
3. A method according to Claim 1 or Claim 2, wherein the step of forming a wet undercoat layer comprises the formation of a layer that varies spatially with the pattern of ink droplets to be deposited.
4. A method according to Claim 3, wherein the undercoat layer is formed on selected regions of the substrate but not on other regions, the selection of regions to receive an undercoat being dependent upon the pattern of ink droplets.
5. A method according to Claim 3, wherein the thickness of the undercoat layer varies spatially with the pattern of ink droplets to be deposited.
6. A method according to any one of the preceding claims, wherein the thickness of the undercoat layer varies generally inversely with the number of ink droplets to be deposited in a local region.
7. A method according to Claim 6, in which it is arranged that the total thickness of undercoat plus ink, remains sensibly constant over at least a region of the substrate.

- 11 -

8. A method according to Claim 6 or Claim 7, wherein the variation in the thickness of the undercoat layer with the pattern of deposited ink droplets, is disabled in regions where the print content to be represented by the pattern of ink is determined to comprise text or other high spatial frequency matter.
9. A method according to any one of the preceding claims, wherein the undercoat layer is UV curable.
10. A method according to any one of the preceding claims, wherein the ink includes a diluent and the undercoat layer is formed essentially of the same diluent.
11. Ink jet printing apparatus comprising a substrate path; an undercoat station for forming a UV curable undercoat layer on a substrate; at least one ink jet printhead positioned downstream of the undercoat station in the substrate path for depositing ink droplets onto the undercoat whilst it remains wet; and a UV curing station downstream in the substrate path of the or each printhead.
12. A method of ink jet printing on a substrate, comprising the steps of ink jet printing an undercoat layer on the substrate; the thickness of that layer varying across the substrate in accordance with the thickness of the ink to be deposited, and ink jet printing ink onto the undercoat.
13. A method according to Claim 12, further comprising the step of signal processing a print data file to provide a luminance map indicative of the thickness of the ink to be deposited; and utilising said luminance map to determine the desired thickness of undercoat.
14. A method according to Claim 12, wherein the undercoat layer remains wet as the ink droplets are deposited.

- 12 -

15. A method according to Claim 12, wherein the undercoat layer is formed on selected regions of the substrate but not on other regions, the selection of regions to receive an undercoat being dependent upon the pattern of ink droplets.
16. A method according to any one Claims 12 to 15, wherein the thickness of the undercoat layer varies generally inversely with the number of ink droplets to be deposited in a local region.
17. A method according to Claim 16, in which it is arranged that the total thickness of undercoat plus ink, remains sensibly constant over the substrate.
18. A method according to Claim 16 or Claim 17, wherein the variation in the thickness of the undercoat layer with the pattern of deposited ink droplets, is disabled in regions where the print content to be represented by the pattern of ink is determined to comprise text or other high spatial frequency matter.
19. A method according to any one of Claims 12 to 18, wherein the variation in thickness of the undercoat layer serves to define pits for receiving droplets of ink.
20. A method of ink jet printing utilising at least two print components having different optical density, comprising the steps of depositing at respective elemental print areas varying numbers of droplets of the respective print components, wherein the relative numbers of ink droplets from the respective print components are controlled to produce the desired print density and wherein the aggregate number of droplets deposited at each elemental print area is substantially constant.
21. A method according to Claim 20, wherein one print component is clear.

- 13 -

22. A method according to Claim 20, wherein one print component defines a white undercoat.
23. A method according to Claim 20, wherein one print component defines a clear topcoat.

1 / 1




Fig 1




Fig 2



Fig 3

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 99/03883

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B41J2/21

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B41J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 671 268 A (SONY CORP) 13 September 1995 (1995-09-13)	1,2
A	abstract page 7, line 55 -page 8, line 7 claims; figure 2	3-22
X	EP 0 657 849 A (HEWLETT PACKARD CO) 14 June 1995 (1995-06-14)	1
A	abstract; claims EP 0 847 872 A (CANON KK) 17 June 1998 (1998-06-17)	3-8, 12, 14-23
	abstract page 5, line 44 -page 6, line 24 figure 7	
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "S" document member of the same patent family

Date of the actual completion of the international search

7 March 2000

Date of mailing of the international search report

16/03/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Didenot, B

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 99/03883

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 04964 A (COATES BROTHERS PLC ;CAIGER NIGEL ANTONY (GB); COCKETT MICHAEL ANT) 13 February 1997 (1997-02-13) the whole document	9,11
A	PATENT ABSTRACTS OF JAPAN vol. 1996, no. 07, 31 July 1996 (1996-07-31) & JP 08 072229 A (CANON INC), 19 March 1996 (1996-03-19) abstract & US 5 959 641 A (YOKOI KATSUYUKI) 28 September 1999 (1999-09-28) abstract figures 2,3	1-9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No
PCT/GB 99/03883

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0671268	A	13-09-1995	JP 7096603 A US 5644350 A CN 1113078 A,B WO 9503940 A	11-04-1995 01-07-1997 06-12-1995 09-02-1995
EP 0657849	A	14-06-1995	DE 69422483 D JP 7195823 A US 5635969 A	10-02-2000 01-08-1995 03-06-1997
EP 0847872	A	17-06-1998	JP 10166559 A	23-06-1998
WO 9704964	A	13-02-1997	AU 6525396 A EP 0842051 A	26-02-1997 20-05-1998
JP 08072229	A	19-03-1996	US 5959641 A	28-09-1999

THIS PAGE BLANK (USPTO)